



I/O PORTS:

NO.	SYMBOL
1	VLCD
2	V2
3	V3
4	V4
5	V5
6	VSS
7	GND
8	VDD
9	FRM
10	CP
11	DF
12	LOAD
13	D.OFF
14	GND
15	D3
16	D2
17	D1
18	D0

- NOTES:
1. DISPLAY TYPE: FSTN
 2. VIEWING DIRECTION: 9:00
 3. POLARIZER MODE: TRANSPARENT/POSITIVE
 4. DRIVE METHOD: 1/240 DUTY 1/16 BIAS
 5. LCD OPERATING VOLTAGE: 22.5V VDD=3.0V
 6. OPERATING TEMP. : 20° C--+70° C
 7. STORAGE TEMP. : -30° C--+80° C
 8. CONNECTOR: FPC
 9. DRIVER: NT7701 & NT7709
 10. BACKLIGHT : WITHOUT
 11. UNMARKED TOLERANCES: ±0.3mm
 12. THE CONTROLLED DIMENSION MASK TO BE:
 13. REQUIREMENTS ON ENVIRONMENTAL PROTECTION: RoHS

Jasonic Technology Limited

DRAWN BY:	TITLE: JTG320240ACIG-01	
ME CHECKED BY:	DWG NO: G-1	UNT: mm
EE CHECKED BY:	SCALE:	SHEET NO: 1 OF 1
APPROVED BY:		