



NOTE:
 1. () :REFERENCE DIMENSION.
 2. □ :IMPORTANT DIMENSION.



No.	Symbol
1	PMARK
2	RESET
3	V10-1.8V
4	VDD-2.8V
5	GND
6	LEDA
7	LEDK
8	GND
9	NC
10	NC
11	NC
12	NC
13	NC
14	NC
15	NC
16	NC
17	NC
18	GND
19	TDNO
20	TDP0
21	GND
22	TCN
23	TCP
24	GND

- NOTES:
- General Tolerance: ±0.3
 - () reference dimension.
 - Recommended case open area should be less than module VA
 - Recommended cushion adherent area: TP VA+1.6mm
 - RoHS must be compliant.

VER.	SYMBOL	AMENDMENT	SIGN	DATE	CUSTOMER'S APPROVAL
V00		First issue		2016.12.02	

DRAWN	ME.CHECKED	EE.CHECKED	APPROVED
-------	------------	------------	----------

TITLE	MODULE SPEC.
DRAWING NO.	JT154GPAXV02
UNIT	mm
3rd Angle	SCALE
	SHEET 1 OF 1

Display Type	TFI,NORMAL block TRANSMISSIVE
Optimum Viewing Direction	Full viewing
TOP Polarizer Type	
LCD Driver IC	ST7796S
Operating Voltage	
Operating Temperature	-20°C TO 70°C
Storage Temperature	-30°C TO 80°C
Interface	Mipi interface
Backlight	2-CHIP WHITE LED
Surface Luminance	400 CD/M2
Write X/Y	TBD